

ONIX

オニキス

途切れたような不規則なリブ柄が特徴のジャカード織りのドレープ生地です。ボリューム感があり、きめの細かい経糸を組み合わせることで、華やかな印象の生地になりました。エレガントな雰囲気とソフトな手触りを備えた魅力的なアイテムは、住宅だけでなく公共施設でのご使用にも最適です。



| | |
|--------------|--|
| 商品カテゴリ | ドレープ |
| 色数 | 6 |
| 特注色 | - 120 m よりご注文承ります |
| 組成 | 100% 難燃ポリエステル (Trevira cs) |
| 生地幅 | 300 cm |
| 横使い可能 | 横使い可能 |
| リピート | 巾 28.0 cm 高さ 28.0 cm |
| 重さ | 125 g/m ² |
| 防炎性能 | 防炎 |
| その他の用途 | |
| お取り扱い | |
| 水洗い収縮率 | 0.5% |
| ドライクリーニング収縮率 | 0.5% |
| 耐光堅牢度 | 5 |
| 認定/試験* | Fire Test Norm BS 5867 Fire Test Japan Fire Test M1 Fire Test DIN 4102 B1 |



ONIX

オニキス



Col. 0501



Col. 0502



Col. 0503



Col. 0504




Col. 0505





Col. 0506


CARE SYMBOLS FOR TEXTILES


Washing


 Normal process 95 ° C

 Mild process 60 ° C

 Mild process 40 ° C


 Mild process 30 ° C


 Wash by hand, max. temperature 40 ° C

 Do not wash


The numbers in the washing tub specify the maximum temperature in ° C which must not be exceeded. The bar underneath the wash tub characterizes a milder cycle with reduced mechanical action.


Chlorine-based bleaching

 Any bleaching agent allowed

 Do not bleach

Tumble drying


 Tumble drying possible lower temperature 60 ° C


 Do not tumble dry


The numbers of dots indicates the severity as regards to temperature of the tumble drying treatment.

Ironing (hand iron)

 Iron at maximum sole-plate temperature 200 ° C


 Iron at a medium sole-plate temperature 150 ° C. Take care when using a steam iron


 Iron at a low sole-plate temperature 110 ° C. Take care when using a steam iron


 Do not iron


The number of dots indicates the severity as regards to temperature of the handiron.

Dry-cleaning

 Professional dry cleaning with tetrachloroethene and hydrocarbons mild process


 Professional dry cleaning with hydrocarbons mild process


 Do not dry clean

 Professional wet cleaning normal process

The letters within the circle specify the solvents that can be used. The bar under the circle indicates that certain limitations in the drycleaning process are required. These may concern mechanical action and/or drying temperature and/or water addition in the solvent. No selfservice cleaning allowed.

















Gecko















 Cleaning with window wiper (Unger method)

 Cleaning by "Spray Extraction" method by machine

SYMBOLS AND PRODUCT INFORMATION

Product information

| | |
|--|--|
|  | Inherently flame retardant |
|  | Width (cm) |
|  | Can be railroded (only valid for curtains) |
|  | Has to be railroded |
|  | Must not be railroded |
|  | Repeat in warp direction |
|  | Repeat in weft direction |
|  | Weight (g/m2) |
|  | Yarn dyed |
|  | Piece dyed |
|  | Knitted |
|  | Woven |
|  | Warp print |
|  | Screen print/burnout |
|  | Metalized on one side |
|  | Pearl reflex |

| | |
|---|---|
|  | Free from harmful substances / Oddy |
|  | Antimicrobial (counteracts colonisation and multiplying of micro organisms and odours.) |
|  | light transmission level Tv, n-h |
|  | light reflection level Pv, n-h |
|  | light absorption level Av |
|  | UV transmission level Tuv |
|  | solar transmission level Te, n-h |
|  | solar reflection level Pe, n-h |
|  | solar absorption level Ae |
|  | Openess factor |
|  | Usable in a bathroom/wet room (Plissee) |
|  | Stain resistant (Plissee) |
|  | Various articles are only available in complete picture repeats. The price is quoted per repeat in each case. |
|  | Additional product information |

Material information

| | |
|---------------|---|
| AC | Acetate |
| CA | Hemp |
| CO | Cotton |
| EA | Elasthan |
| GL | Glass fibre |
| LI | Linen |
| MD | Modal |
| ME | Metal |
| PA | Polyamide |
| PC | Acrylic |
| PE | Polyethylene |
| PI | Paper |
| PL | Polyester |
| PLF | Flameretardant polyester |
| PLF CS | Flameretardant polyester (Trevira CS) |
| PN | Polycarbonat |
| PP | Polypropylene |
| PU | Polyurethan |
| RA | Ramie |
| SE | Silk |
| SI | Silicone |
| TR | Different material (wood, paper, feathers etc.) |
| VI | Viscose |
| WM | Wool Mohair |
| WV | Wool |

SYMBOLS AND PRODUCT INFORMATION

Intended purposes



Curtains/Sheers



Roller blinds (colours see separate roller blind collection)



Panels (process the panels in warp direction to get optimal hang properties)



Vertical blinds



Roman blinds



Upholstery (for heavy use in contract application).
Martindale > 30'000



Upholstery (for heavy use in domestic application/for normal use in contract application). 20'000 < Martindale < 30'000



Upholstery (for normal use in domestic application/for careful use in contract application). Martindale < 20'000



Loose cover for careful use in domestic application.
Martindale < 5'000



Bedspreads



Table cloth domestic use



Wallcovering



Textile wallpaper (can be paper backed, minimum quantity)



Cushion



Acoustical fabrics



Adhesive Textiles/Gecko/Gecko in the Box



Fabrics with very high lightfastness for indoor and outdoor use



Blackout



Reverso



Plissé



Comb plissé