


CALMA

**カルマ**

表裏で色の異なるドレープファブリックです。ノブールなピンストライプと立体感のある畝のある織りが特徴です。カーテンの他、ベッドスプレッドなどにも優雅な雰囲気でおすすめてです。



商品カテゴリー	ベッドスプレッド用生地
色数	10
特注色	- 300 m よりご注文承ります
組成	100% 難燃ポリエステル ( Trevira cs)
生地幅	280 cm
横使い可能	横使い可能
リピート	高さ 11.0 cm
重さ	392 g/m <sup>2</sup>
防炎性能	防炎
その他の用途	
お取り扱い	
水洗い収縮率	1.5%
ドライクリーニング収縮率	1.5%
吸音	吸音値 0.95
耐摩耗制	5'000 マーチンデール
ピリング	4-5
耐光堅牢度	6-7
認定/試験*	Fire Test DIN 4102 B1 Fire Test Japan Fire Test Norm BS 5867 Sound absorption ISO 354 / ISO 11654 Flow resistance DIN EN 29053



\*認定書や試験結果は、ウェブサイト内の各商品ページ、download (ダウンロード) よりご覧いただけます。



CALMA

カルマ




Col. 0301




Col. 0302



Col. 0303



Col. 0304



Col. 0305



Col. 0306



Col. 0307



Col. 0308




Col. 0309





Col. 0310


# CARE SYMBOLS FOR TEXTILES


## Washing


 Normal process 95 ° C

 Mild process 60 ° C

 Mild process 40 ° C


 Mild process 30 ° C


 Wash by hand, max. temperature 40 ° C

 Do not wash


The numbers in the washing tub specify the maximum temperature in ° C which must not be exceeded. The bar underneath the wash tub characterizes a milder cycle with reduced mechanical action.


## Chlorine-based bleaching

 Any bleaching agent allowed

 Do not bleach


## Tumble drying


 Tumble drying possible lower temperature 60 ° C


 Do not tumble dry


The numbers of dots indicates the severity as regards to temperature of the tumble drying treatment.

## Ironing (hand iron)

 Iron at maximum sole-plate temperature 200 ° C


 Iron at a medium sole-plate temperature 150 ° C. Take care when using a steam iron


 Iron at a low sole-plate temperature 110 ° C. Take care when using a steam iron


 Do not iron

The number of dots indicates the severity as regards to temperature of the handiron.

## Dry-cleaning

 Professional dry cleaning with tetrachloroethene and hydrocarbons mild process


 Professional dry cleaning with hydrocarbons mild process


 Do not dry clean

 Professional wet cleaning normal process

The letters within the circle specify the solvents that can be used. The bar under the circle indicates that certain limitations in the drycleaning process are required. These may concern mechanical action and/or drying temperature and/or water addition in the solvent. No selfservice cleaning allowed.

















## Gecko















 Cleaning with window wiper (Unger method)

 Cleaning by "Spray Extraction" method by machine

# SYMBOLS AND PRODUCT INFORMATION

## Product information

	Inherently flame retardant
	Width (cm)
	Can be railroded (only valid for curtains)
	Has to be railroded
	Must not be railroded
	Repeat in warp direction
	Repeat in weft direction
	Weight (g/m2)
	Yarn dyed
	Piece dyed
	Knitted
	Woven
	Warp print
	Screen print/burnout
	Metalized on one side
	Pearl reflex

	Free from harmful substances / Oddy
	Antimicrobial (counteracts colonisation and multiplying of micro organisms and odours.)
	light transmission level Tv, n-h
	light reflection level Pv, n-h
	light absorption level Av
	UV transmission level Tuv
	solar transmission level Te, n-h
	solar reflection level Pe, n-h
	solar absorption level Ae
	Openess factor
	Usable in a bathroom/wet room (Plissee)
	Stain resistant (Plissee)
	Various articles are only available in complete picture repeats. The price is quoted per repeat in each case.
	Additional product information

## Material information

<b>AC</b>	Acetate
<b>CA</b>	Hemp
<b>CO</b>	Cotton
<b>EA</b>	Elasthan
<b>GL</b>	Glass fibre
<b>LI</b>	Linen
<b>MD</b>	Modal
<b>ME</b>	Metal
<b>PA</b>	Polyamide
<b>PC</b>	Acrylic
<b>PE</b>	Polyethylene
<b>PI</b>	Paper
<b>PL</b>	Polyester
<b>PLF</b>	Flameretardant polyester
<b>PLF CS</b>	Flameretardant polyester (Trevira CS)
<b>PN</b>	Polycarbonat
<b>PP</b>	Polypropylene
<b>PU</b>	Polyurethan
<b>RA</b>	Ramie
<b>SE</b>	Silk
<b>SI</b>	Silicone
<b>TR</b>	Different material (wood, paper, feathers etc.)
<b>VI</b>	Viscose
<b>WM</b>	Wool Mohair
<b>WV</b>	Wool

# SYMBOLS AND PRODUCT INFORMATION

## Intended purposes



Curtains/Sheers



Roller blinds (colours see separate roller blind collection)



Panels (process the panels in warp direction to get optimal hang properties)



Vertical blinds



Roman blinds



Upholstery (for heavy use in contract application).  
Martindale > 30'000



Upholstery (for heavy use in domestic application/for normal use in contract application). 20'000 < Martindale < 30'000



Upholstery (for normal use in domestic application/for careful use in contract application). Martindale < 20'000



Loose cover for careful use in domestic application.  
Martindale < 5'000



Bedspreads



Table cloth domestic use



Wallcovering



Textile wallpaper (can be paper backed, minimum quantity)



Cushion



Acoustical fabrics



Adhesive Textiles/Gecko/Gecko in the Box



Fabrics with very high lightfastness for indoor and outdoor use



Blackout



Reverso



Plissé



Comb plissé