

UNIVERSAL V

ユニバーサルV

高密度な平織りのファブリックUNIVERSAL(ユニバーサル)は、難燃系トレピラCSを使った定番のベストセラーファブリックです。トレンドに左右されないマットでクリアなファブリックで、柔らかい肌触りと流れるような風合いを持ちます。多色のカラーを取りそろえた後染めファブリックです。



商品カテゴリー	ドレープ
色数	40
特注色	- 240 m よりご注文承ります - from 120 m Price upon request
組成	100% 難燃ポリエステル (Trevira cs)
生地幅	300 cm
特記事項	横使い可能
重さ	120 g/m ²
防炎性能	防炎
その他の用途	
お取り扱い	
水洗い収縮率	1%
水洗い収縮率	0.5%
ドライクリーニング収縮率	1%
吸音	吸音値 0.65
耐光堅牢度	6
認定/試験*	Fire Test DIN 4102 B1 Fire Test SNV 198898 Fire Test NFPA701 Fire Test Japan Fire Test Italien Light transmission Sound absorption Flow resistance



UNIVERSAL V


ユニバーサル V


					
Col. 0301	Col. 0302	Col. 0305	Col. 0306	Col. 0307	Col. 0308
					
Col. 0309	Col. 0310	Col. 0311	Col. 0312	Col. 0313	Col. 0314
					
Col. 0315	Col. 0318	Col. 0325	Col. 0331	Col. 0332	Col. 0342
					
Col. 0401	Col. 0402	Col. 0403	Col. 0404	Col. 0405	Col. 0406
					
Col. 0407	Col. 0408	Col. 0409	Col. 0410	Col. 0411	Col. 0412
					
Col. 0413	Col. 0414	Col. 0415	Col. 0416	Col. 0417	Col. 0418
					
Col. 0419	Col. 0420	Col. 0421	Col. 0422	Col. 0303*	Col. 0304*
					
Col. 0316*	Col. 0317*	Col. 0319*	Col. 0320*	Col. 0321*	Col. 0322*
					
Col. 0323*	Col. 0324*	Col. 0326*	Col. 0327*	Col. 0328*	Col. 0329*
					
Col. 0330*	Col. 0333*	Col. 0334*	Col. 0335*	Col. 0336*	Col. 0337*
					
Col. 0338*	Col. 0339*	Col. 0340*	Col. 0341*	Col. 0343*	Col. 0344*
					
Col. 0345*	Col. 0346*	Col. 0347*	Col. 0348*	Col. 0349*	Col. 0350*
					
Col. 0351*	Col. 0352*				


ロットにより色味が多少異なる場合があります。お問い合わせください。
* 廃番のため在庫限りとなります。


CARE SYMBOLS FOR TEXTILES


Washing


 Normal process 95 ° C

 Mild process 60 ° C

 Mild process 40 ° C


 Mild process 30 ° C


 Wash by hand, max. temperature 40 ° C

 Do not wash


The numbers in the washing tub specify the maximum temperature in ° C which must not be exceeded. The bar underneath the wash tub characterizes a milder cycle with reduced mechanical action.


Chlorine-based bleaching

 Any bleaching agent allowed

 Do not bleach


Tumble drying


 Tumble drying possible lower temperature 60 ° C


 Do not tumble dry


The numbers of dots indicates the severity as regards to temperature of the tumble drying treatment.

Ironing (hand iron)

 Iron at maximum sole-plate temperature 200 ° C


 Iron at a medium sole-plate temperature 150 ° C. Take care when using a steam iron


 Iron at a low sole-plate temperature 110 ° C. Take care when using a steam iron


 Do not iron


The number of dots indicates the severity as regards to temperature of the handiron.

Dry-cleaning

 Professional dry cleaning with tetrachloroethene and hydrocarbons mild process


 Professional dry cleaning with hydrocarbons mild process


 Do not dry clean

 Professional wet cleaning normal process

The letters within the circle specify the solvents that can be used. The bar under the circle indicates that certain limitations in the drycleaning process are required. These may concern mechanical action and/or drying temperature and/or water addition in the solvent. No selfservice cleaning allowed.

















Gecko

















 Cleaning with window wiper (Unger method)

 Cleaning by "Spray Extraction" method by machine

SYMBOLS AND PRODUCT INFORMATION

Product information

	Inherently flame retardant
	Width (cm)
	Can be railroded (only valid for curtains)
	Has to be railroded
	Must not be railroded
	Repeat in warp direction
	Repeat in weft direction
	Weight (g/m2)
	Yarn dyed
	Piece dyed
	Knitted
	Woven
	Warp print
	Screen print/burnout
	Metalized on one side
	Pearl reflex

	Free from harmful substances / Oddy
	recycled material
	Symbol for returning of used fabrics. Only valid in CH and DE.
	Antimicrobial (counteracts colonisation and multiplying of micro organisms and odours.)
	light transmission level Tv, n-h
	light reflection level Pv, n-h
	light absorption level Av
	UV transmission level Tuv
	solar transmission level Te, n-h
	solar reflection level Pe, n-h
	solar absorption level Ae
	Openess factor
	Usable in a bathroom/wet room (Plissee)
	Stain resistant (Plissee)
	Various articles are only available in complete picture repeats. The price is quoted per repeat in each case.
	Additional product information

Material information

AC	Acetate
CA	Hemp
CO	Cotton
EA	Elasthan
GL	Glass fibre
LI	Linen
MD	Modal
ME	Metal
PA	Polyamide
PC	Acrylic
PE	Polyethylene
PI	Paper
PL	Polyester
PLF	Flameretardant polyester
PLF CS	Flameretardant polyester (Trevira CS)
PLF CS ECO	
PN	Polycarbonat
PP	Polypropylene
PU	Polyurethan
RA	Ramie
SE	Silk
SI	Silicone
TR	Different material (wood, paper, feathers etc.)
VI	Viscose
WM	Wool Mohair
WV	Wool

SYMBOLS AND PRODUCT INFORMATION

Intended purposes



Curtains/Sheers



Roller blinds (colours see separate roller blind collection)



Panels (process the panels in warp direction to get optimal hang properties)



Vertical blinds



Roman blinds



Upholstery (for heavy use in contract application).
Martindale > 30'000



Upholstery (for heavy use in domestic application/for normal use in contract application). 20'000 < Martindale < 30'000



Upholstery (for normal use in domestic application/for careful use in contract application). Martindale < 20'000



Loose cover for careful use in domestic application.
Martindale < 5'000



Bedspreads



Table cloth domestic use



Wallcovering



Textile wallpaper (can be paper backed, minimum quantity)



Cushion



Acoustical fabrics



Adhesive Textiles/Gecko/Gecko in the Box



Fabrics with very high lightfastness for indoor and outdoor use



Blackout



Reverso



Plissé



Comb plissé