

DIMMER IV-300

ディマー III (300 cm)

クリエーションバウマンを代表する遮光生地DIMMER(ディマー)は生地幅300 cmでもご用意しています。流れるような美しいドレープと遮光性を併せ持ち、機能性と美しさを兼ね備えています。織りの秘密は、特別に開発された糸にあります。糸の重さが10kmの長さで1 g以下である極細のほんの少しカーブした糸によって、高密度に織ることに成功し遮光効果を出しています。色によって遮光等級が異なります。



商品カテゴリー	遮光生地
色数	19
組成	100% 難燃ポリエステル (Trevira cs)
生地幅	300 cm
横使い可能	横使い可能
重さ	260 g/m ²
防災性能	防災
その他の用途	
お取り扱い	
水洗い収縮率	0.5%
ドライクリーニング収縮率	1%
吸音	吸音値 0.60
耐摩耗制	23'000 マーチンデール
ピリング	4-5
耐光堅牢度	6-7
認定/試験*	Fire Test DIN 4102 B1 Fire Test SNV 198898 Fire Test Japan Fire Test M1 Fire Test Norm BS 5867 Sound absorption ISO 354 / ISO 11654 Flow resistance DIN EN 29053 Light transmission
特記事項	- Dim-out: Die Farben sind entsprechend ihres Abdunkelungsverhaltens in drei Gruppen unterteilt: light, regular und dark.



DIMMER IV-300

ディマー III (3 0 0 c m)


					
Col. 2101	Col. 2102	Col. 2103	Col. 2105	Col. 2106	Col. 2107
					
Col. 2109	Col. 2110	Col. 2201	Col. 2202	Col. 2203	Col. 2204
	Col. 2226*				
Col. 2207		Col. 2301	Col. 2302	Col. 2303	Col. 2305
Col. 2401	Col. 2402	Col. 2403	Col. 2404	Col. 2405	Col. 2406
Col. 2407					


ロットにより色味が多少異なる場合があります。お問い合わせください。

* 廃番のため在庫限りとなります。


CARE SYMBOLS FOR TEXTILES


Washing


 Normal process 95 ° C

 Mild process 60 ° C

 Mild process 40 ° C


 Mild process 30 ° C


 Wash by hand, max. temperature 40 ° C

 Do not wash


The numbers in the washing tub specify the maximum temperature in ° C which must not be exceeded. The bar underneath the wash tub characterizes a milder cycle with reduced mechanical action.


Chlorine-based bleaching

 Any bleaching agent allowed

 Do not bleach

Tumble drying


 Tumble drying possible lower temperature 60 ° C


 Do not tumble dry


The numbers of dots indicates the severity as regards to temperature of the tumble drying treatment.

Ironing (hand iron)

 Iron at maximum sole-plate temperature 200 ° C


 Iron at a medium sole-plate temperature 150 ° C. Take care when using a steam iron


 Iron at a low sole-plate temperature 110 ° C. Take care when using a steam iron


 Do not iron


The number of dots indicates the severity as regards to temperature of the handiron.

Dry-cleaning

 Professional dry cleaning with tetrachloroethene and hydrocarbons mild process


 Professional dry cleaning with hydrocarbons mild process


 Do not dry clean

 Professional wet cleaning normal process

The letters within the circle specify the solvents that can be used. The bar under the circle indicates that certain limitations in the drycleaning process are required. These may concern mechanical action and/or drying temperature and/or water addition in the solvent. No selfservice cleaning allowed.

















Gecko
















 Cleaning with window wiper (Unger method)

 Cleaning by "Spray Extraction" method by machine

SYMBOLS AND PRODUCT INFORMATION

Product information

	Inherently flame retardant
	Width (cm)
	Can be railroded (only valid for curtains)
	Has to be railroded
	Must not be railroded
	Repeat in warp direction
	Repeat in weft direction
	Weight (g/m2)
	Yarn dyed
	Piece dyed
	Knitted
	Woven
	Warp print
	Screen print/burnout
	Metalized on one side
	Pearl reflex

	Free from harmful substances / Oddy
	
	Antimicrobial (counteracts colonisation and multiplying of micro organisms and odours.)
	light transmission level Tv, n-h
	light reflection level Pv, n-h
	light absorption level Av
	UV transmission level Tuv
	solar transmission level Te, n-h
	solar reflection level Pe, n-h
	solar absorption level Ae
	Openess factor
	Usable in a bathroom/wet room (Plissee)
	Stain resistant (Plissee)
	Various articles are only available in complete picture repeats. The price is quoted per repeat in each case.
	Additional product information

Material information

AC	Acetate
CA	Hemp
CO	Cotton
EA	Elasthan
GL	Glass fibre
LI	Linen
MD	Modal
ME	Metal
PA	Polyamide
PC	Acrylic
PE	Polyethylene
PI	Paper
PL	Polyester
PLF	Flameretardant polyester
PLF CS	Flameretardant polyester (Trevira CS)
PN	Polycarbonat
PP	Polypropylene
PU	Polyurethan
RA	Ramie
SE	Silk
SI	Silicone
TR	Different material (wood, paper, feathers etc.)
VI	Viscose
WM	Wool Mohair
WV	Wool

SYMBOLS AND PRODUCT INFORMATION

Intended purposes



Curtains/Sheers



Roller blinds (colours see separate roller blind collection)



Panels (process the panels in warp direction to get optimal hang properties)



Vertical blinds



Roman blinds



Upholstery (for heavy use in contract application).
Martindale > 30'000



Upholstery (for heavy use in domestic application/for normal use in contract application). 20'000 < Martindale < 30'000



Upholstery (for normal use in domestic application/for careful use in contract application). Martindale < 20'000



Loose cover for careful use in domestic application.
Martindale < 5'000



Bedspreads



Table cloth domestic use



Wallcovering



Textile wallpaper (can be paper backed, minimum quantity)



Cushion



Acoustical fabrics



Adhesive Textiles/Gecko/Gecko in the Box



Fabrics with very high lightfastness for indoor and outdoor use



Blackout



Reverso



Plissé



Comb plissé

