

UNION II

Opaque curtain fabric in Trevira CS with a soft feel and fluid drape qualities. The airily light fabric lets daylight into the interior, whilst being completely dense to intrusive stares. Union II can, if needed, be pushed together to form a small space saving gathered parcel. The colour palette encompasses light, neutral and dark tones along with vibrant accent colours.




Use:	Dense curtain fabric
Number of colours:	24 Special colours available from 220 m / 240 yds upwards.
Material:	100% Flameretardant polyester (Trevira CS)
Fabric width:	310 cm/122 inch/3.39 yard
Can be railroaded:	Can be railroaded
Weight:	63 g/m ²
Flame-retardant properties:	
Additional use:	
Care:	
Washing (length shrinkage):	1%
Washing (length shrinkage):	0.5%
Dry cleaning (length shrinkage):	1%
Light fastness:	5-6
Certificates / tests:	Fire Test DIN 4102 B1 Fire Test Japan

*all testing reports can be downloaded from our website under product details



UNION II



Col. 0201



Col. 0202



Col. 0203



Col. 0204



Col. 0211



Col. 0212



Col. 0213



Col. 0216




Col. 0221



Col. 0222



Col. 0223



Col. 0224



Col. 0225



Col. 0226



Col. 0227



Col. 0228



Col. 0229



Col. 0230



Col. 0231



Col. 0232




Col. 0233



Col. 0234



Col. 0235



Col. 0236

Note:

Colours may vary. Please ask for our colour samples.

* As long as stock lasts

CARE SYMBOLS FOR TEXTILES

Washing (wash tub)



Normal process 95°



Mild process 95°



Normal process 60°



Mild process 60°



Normal process 40°



Mild process 40°



Very mild process 30°



Hand wash



Do not wash

The numbers in the washing tub specify the maximum temperature in °C which must not be exceeded. The bar underneath the wash tub characterizes a milder cycle with reduced mechanical action.

Ironing (hand iron)



Iron at maximum sole-plate temperature



Iron at a medium sole-plate temperature. Take care when using a steam iron



Iron at a low sole-plate temperature. Take care when using a steam iron



Do not iron

The number of dots indicates the severity as regards to temperature of the handiron.

Chlorine-based bleaching (triangle)



Chlorine-based bleaching allowed



Do not use chlorine-based bleach

Tumble drying (circle in a square)



Drying at a lower temperature setting



Do not tumble dry

The numbers of dots indicates the severity as regards to temperature of the tumble drying treatment.

Dry-cleaning (circle)



Self-service cleaning also allowed (A)



Drycleanable



Drycleanable



Self-service cleaning not allowed (F)



Self-service cleaning not allowed (F2)



Do not dry clean



Mild professional wet-cleaning

The letters within the circle specify the solvents that can be used. The bar under the circle indicates that certain limitations in the drycleaning process are required. These may concern mechanical action and/or drying temperature and/or water addition in the solvent. – No selfservice cleaning allowed.

Gecko



















Cleaning with window wiper (Unger method)















Cleaning by "Spray Extraction" method by machine

SYMBOLS AND PRODUCT INFORMATION

Product information

	Inherently flame retardant
	Width (cm)
	Can be railroaded (only valid for curtains)
	Has to be railroaded
	Must not be railroaded
	Repeat in warp direction
	Repeat in weft direction
	Weight (g/m2)
	Yarn dyed
	Piece dyed
	Knitted
	Woven
	Warp print
	Screen print/burnout
	Metalized on one side
	Free from harmful substances / Oddy

	Antimicrobial (counteracts colonisation and multiplying of micro organisms and odours.)
	light transmission level Tv, n-h
	light transmission level Tv, n-nn
	light transmission level Tv, n-dif
	light reflection level Pv, n-h
	light absorption level Av
	UV transmission level Tuv
	solar transmission level Te, n-h
	solar reflection level Pe, n-h
	solar absorption level Ae
	Various articles are only available in complete picture repeats. The price is quoted per repeat in each case.
	Additional product information

Material information

AC	Acetate
CA	Hemp
CO	Cotton
EA	Elasthan
GL	Glass fibre
LI	Linen
MD	Modal
ME	Metal
PA	Polyamide
PC	Acrylic
PE	Polyethylene
PI	Paper
PL	Polyester
PLF	Flameretardant polyester
PLF CS	Flameretardant polyester (Trevira CS)
PN	Polycarbonat
PP	Polypropylene
PU	Polyurethan
RA	Ramie
SE	Silk
SI	Silicone
TR	Different material (wood, paper, feathers etc.)
VI	Viscose
WM	Wool Mohair
WV	Wool

SYMBOLS AND PRODUCT INFORMATION

Intended purposes



Curtains/Sheers



Roller blinds (colours see separate roller blind collection)



Panels (process the panels in warp direction to get optimal hang properties)



Vertical blinds



Roman blinds



Upholstery (for heavy use in contract application).
Martindale > 30'000



Upholstery (for heavy use in domestic application/for normal
use in contract application). 20'000 < Martindale < 30'000



Upholstery (for normal use in domestic application/for careful
use in contract application). Martindale < 20'000



Loose cover for careful use in domestic application.
Martindale < 5'000



Bedspreads



Table cloth domestic use



Wallcovering



Textile wallpaper (can be paper backed, minimum quantity)



Cushion



Acoustical fabrics



Adhesive Textiles/Gecko/Gecko in the Box



Fabrics with very high lightfastness for indoor and outdoor use



Reverso