

SCALINO

スカリーノ

フィリグリーのように立体的に施したプリーツと刺繍のダイヤモンド柄のラインが、まるでハンドスケッチの線のようにファブリックに広がるデザインです。ファブリックの端はアクセントカラーの精巧なコード刺繍で仕上げています。6色をご用意しております。



商品カテゴリー	ケースメント
色数	6
特注色	- 90 m よりご注文承ります
組成	93% 麻 7% 綿
生地幅	290 cm
特記事項	横使い可能
リピート	巾 290.0 cm 高さ 11.0 cm
重さ	156 g/m <sup>2</sup>
防火性能	非防火 (防火加工可)
その他の用途	
お取り扱い	



水洗い収縮率	2.5%
ドライクリーニング収縮率	2%
耐光堅牢度	6
特記事項	- Optimal kombinierbar mit dem Leinenklassiker Filino Color II.



SCALINO

スカリーノ



Col. 0001



Col. 0002



Col. 0003



Col. 0004




Col. 0005





Col. 0006


# CARE SYMBOLS FOR TEXTILES


## Washing


 Normal process 95 ° C

 Mild process 60 ° C

 Mild process 40 ° C


 Mild process 30 ° C


 Wash by hand, max. temperature 40 ° C

 Do not wash


The numbers in the washing tub specify the maximum temperature in ° C which must not be exceeded. The bar underneath the wash tub characterizes a milder cycle with reduced mechanical action.


## Chlorine-based bleaching

 Any bleaching agent allowed

 Do not bleach


## Tumble drying


 Tumble drying possible lower temperature 60 ° C


 Do not tumble dry


The numbers of dots indicates the severity as regards to temperature of the tumble drying treatment.

## Ironing (hand iron)

 Iron at maximum sole-plate temperature 200 ° C


 Iron at a medium sole-plate temperature 150 ° C. Take care when using a steam iron


 Iron at a low sole-plate temperature 110 ° C. Take care when using a steam iron


 Do not iron


The number of dots indicates the severity as regards to temperature of the handiron.

## Dry-cleaning

 Professional dry cleaning with tetrachloroethene and hydrocarbons mild process


 Professional dry cleaning with hydrocarbons mild process


 Do not dry clean

 Professional wet cleaning normal process

The letters within the circle specify the solvents that can be used. The bar under the circle indicates that certain limitations in the drycleaning process are required. These may concern mechanical action and/or drying temperature and/or water addition in the solvent. No selfservice cleaning allowed.

















## Gecko

















 Cleaning with window wiper (Unger method)

 Cleaning by "Spray Extraction" method by machine

# SYMBOLS AND PRODUCT INFORMATION

## Product information

	Inherently flame retardant
	Width (cm)
	Can be railroded (only valid for curtains)
	Has to be railroded
	Must not be railroded
	Repeat in warp direction
	Repeat in weft direction
	Weight (g/m2)
	Yarn dyed
	Piece dyed
	Knitted
	Woven
	Warp print
	Screen print/burnout
	Metalized on one side
	Pearl reflex

	Free from harmful substances / Oddy
	recycled material
	Symbol for returning of used fabrics. Only valid in CH and DE.
	Antimicrobial (counteracts colonisation and multiplying of micro organisms and odours.)
	light transmission level Tv, n-h
	light reflection level Pv, n-h
	light absorption level Av
	UV transmission level Tuv
	solar transmission level Te, n-h
	solar reflection level Pe, n-h
	solar absorption level Ae
	Openess factor
	Usable in a bathroom/wet room (Plissee)
	Stain resistant (Plissee)
	Various articles are only available in complete picture repeats. The price is quoted per repeat in each case.
	Additional product information

## Material information

<b>AC</b>	Acetate
<b>CA</b>	Hemp
<b>CO</b>	Cotton
<b>EA</b>	Elasthan
<b>GL</b>	Glass fibre
<b>LI</b>	Linen
<b>MD</b>	Modal
<b>ME</b>	Metal
<b>PA</b>	Polyamide
<b>PC</b>	Acrylic
<b>PE</b>	Polyethylene
<b>PI</b>	Paper
<b>PL</b>	Polyester
<b>PLF</b>	Flameretardant polyester
<b>PLF CS</b>	Flameretardant polyester (Trevira CS)
<b>PLF CS ECO</b>	
<b>PN</b>	Polycarbonat
<b>PP</b>	Polypropylene
<b>PU</b>	Polyurethan
<b>RA</b>	Ramie
<b>SE</b>	Silk
<b>SI</b>	Silicone
<b>TR</b>	Different material (wood, paper, feathers etc.)
<b>VI</b>	Viscose
<b>WM</b>	Wool Mohair
<b>WV</b>	Wool

# SYMBOLS AND PRODUCT INFORMATION

## Intended purposes



Curtains/Sheers



Roller blinds (colours see separate roller blind collection)



Panels (process the panels in warp direction to get optimal hang properties)



Vertical blinds



Roman blinds



Upholstery (for heavy use in contract application).  
Martindale > 30'000



Upholstery (for heavy use in domestic application/for normal use in contract application). 20'000 < Martindale < 30'000



Upholstery (for normal use in domestic application/for careful use in contract application). Martindale < 20'000



Loose cover for careful use in domestic application.  
Martindale < 5'000



Bedspreads



Table cloth domestic use



Wallcovering



Textile wallpaper (can be paper backed, minimum quantity)



Cushion



Acoustical fabrics



Adhesive Textiles/Gecko/Gecko in the Box



Fabrics with very high lightfastness for indoor and outdoor use



Blackout



Reverso



Plissé



Comb plissé